

## SPECIFICATION FOR APPROVAL

### 1. Material

|                            |                             |
|----------------------------|-----------------------------|
| Production:                | Nanodust Cores              |
| KDM.P/N:                   | KAM090-060A-E14             |
| AL:                        | 79(nH/N <sup>2</sup> ) ± 8% |
| Material:                  | 60 μ                        |
| Coating Color:             | Khaki                       |
| Coating material:          | epoxy                       |
| Coating Breakdown Voltage: | 1000V, 0.5mA, 2Sec          |




### 2. Physical Characteristics

| Before Coating |                |                | After Coating |             |             | Le(cm) | Ae(cm <sup>2</sup> ) | V(cm <sup>3</sup> ) | W(cm <sup>2</sup> ) | Weight (g) (ref.) | Box Quantity (Pieces) |
|----------------|----------------|----------------|---------------|-------------|-------------|--------|----------------------|---------------------|---------------------|-------------------|-----------------------|
| OD(Max.) in/mm | ID(Min.) in/mm | Ht(Max.) in/mm | OD(Max.) mm   | ID(Min.) mm | Ht(Max.) mm |        |                      |                     |                     |                   |                       |
| 0.902<br>22.90 | 0.551<br>14.00 | 0.551<br>14.00 | 23.62         | 13.39       | 15.00       | 5.670  | 0.608                | 3.454               | 1.407               | 24.1              | 504                   |


### 3. Electrical Parameters(Typical) Temperature(25°C ± 2°C)

| Test Item  | Test Condition   | Value(Typical)               | Test Instrument |
|------------|--|------------------------------|-----------------|
| Inductance | φ 0.8mm/30Ts, 20kHz/1V, I=0A<br>(Evenly full windings)(均匀绕满)           | 71.1 μ H ± 8%                | CH3302          |
| DC-Bias    | φ 0.8mm/30Ts, 20kHz/1V, I=15A(H=100Oe)<br>(Evenly full windings)(均匀绕满) | 43.2 μ H (Min.)              | WK3255B+WK3265B |
| Core Loss  | 50kHz/1000Gs   | 250mW/cm <sup>3</sup> (Max.) | SY-8219         |
| Remarks    | Set the internal resistance of LCR meter to 100 Ω.(电感测试仪内阻设置100 Ω)     |                              |                 |

#### Core Loss Curves(Typical)



#### DC-Bias Curves(Typical)



KDM确认栏  
KDM  
Signature

**科达磁电  
技术部**

客户确认栏  
Customer  
Signature

请在5个工作日内回签承认书，否则此承认书将作为后续订单的OQC标准。若有疑问，请及时联系我司RD部门。  
Please sign back after approval within 5 working days, otherwise this approval sheet would be taken as OQC standard for subsequent orders. If you have any questions, please contact RD department in time.